



Revision number: 1

Purchasing Agent: ROSEMARY FRENCHWOOD

Item: WINTER PATCH MATERIAL "TYPE B" FOB PLANT PICK-UP (SALT LAKE & OREM AREA)

Vendor: 02004J OLDCASTLE MMG, INC.
DBA STAKER PAVING & CONSTRUCTION CO.
P.O. BOX 27598
SALT LAKE CITY UT 84127-0598

Internet Homepage:

Telephone: (801) 455-9686

Fax number: (801) 295-7440

Contact: TERRY CROWTHER

Email address:

Brand/trade name:

Price: SEE ATTACHED PRICE LIST
Terms: NET 30
Effective dates: 07/15/2000 through 07/15/2002
Days required for delivery: N/A
Price guarantee period: 1 YEAR
Minimum order: NONE
Min shipment without charges: N/A FOB PLANT PICKUP
Other conditions:

REVISION #1: PLEASE NOTE CHANGES TO VENDOR NAME, ADDRESS AND PHONE NUMBERS.

This contract covers only those items listed in the price schedule. It is the responsibility of the agency to ensure that other items purchased are invoiced separately. State agencies will place orders directly with the vendor (creating a PG in Finet) and make payments for the same on a PV referencing the original PG. Agencies will return to the vendor any invoice which reflects incorrect pricing.



WINTER PATCH MATERIAL (TYPE B) FOB PLANT PICK UP ONLY \$65.00
/TON

BECK STREET PLANT

DESCRIPTION

821.1.1 GENERAL:

THE MATERIAL UNDER THIS SPECIFICATION SHALL BE A SPECIALIZED WINTER PATCH MATERIAL FOR USE IN REPAIRING POTHOLES DURING WINTER MONTHS.

821.2.1 APPROVED PRODUCTS:

ACCEPTABLE PRODUCTS APPROVED FOR USE IN THESE APPLICATIONS BY THE UTAH DEPARTMENT OF TRANSPORTATION (UDOT) INCLUDE:

- UPM HIGH PERFORMANCE COLD MIX
- QPR 2000 (U.S. PRO TEC0
- PERMA PATCH (NATIONAL PAVING & CONTRACTING)
- BOND - X (SEABOARD ASPHALTS)
- OPTIMIX COLD PATCH MIX

821.2.3 AGGREGATES:

AGGREGATE CAN BE EITHER PROPRIETARY MATERIALS OR LOCAL AGGREGATES. THE USE OF LIMESTONE IS NOT ALLOWED. AGGREGATES MUST MEET THE FOLLOWING GRADATION:

<u>Gradation</u>	<u>% PASSING</u>
1/2"	100
3/8"	90-100
#4	5-55
#8	5-30
#16	0-10
#50	0-5

821.2.3 LIQUID ASPHALT (OIL):

THE LIQUID ASPHALT (OIL) SHALL HAVE CHEMICAL ANTI-STRIPING ADDITIVES MEETING ASTM-D-1664 AND ASTM-D-2027 AND SHALL MEET THE FOLLOWING:



FLASH POINT: 175 DEGREES F MINIMUM
SIBILATE VISCOSITY G 140 DEGREES F; 200-500 SEC
WATER: 0.2 % MAXIMUM

821.2.4 MIXTURE:

THE MIXED MATERIAL SHALL HAVE NO MORE THAN 5% STRIPING AS MEASURED WITH UDOT TEST PROCEDURE 8-945, DYNAMIC STRIPING. MINIMUM LIQUID ASPHALT (OIL) CONTENT SHALL BE 3-7% BY WEIGHT. MATERIALS WHICH EXHIBIT STRIPING OR FREEZING SHALL BE REJECTED.

821.2.5 STOCKPILING:

MATERIALS WHICH EXHIBIT STRIPPING OR FREEZING IN STOCKPILES OR DEEMED UNSATISFACTORY FOR ANY OTHER REASON SHALL BE REJECTED, REMOVED AND REPLACE BY THE SUPPLIER AT HIS/HER EXPENSE WITHIN 10 WORKING DAYS OF NOTIFICATION.

REPORTS:

THE CONTRACTOR WILL SUBMIT YEARLY REPORTS TO THE STATE PURCHASING AGENT (DEBBIE GUNDERSEN) SHOWING QUANTITIES AND DOLLAR VOLUME OF PURCHASES BY EACH AGENCY AND POLITICAL SUBDIVISION. THIS REPORT WILL BE DUE 07/15/2001.

FINET COMMODITY CODE(S): **FOR AGENCY USE ONLY**

74514000000 - ASPHALTIC CONCRETE, COLD LAID